








Compression screw assembly.

Patent number: EP0085493
Publication date: 1983-08-10
Inventor: GRIGGS CALVIN
Applicant: RICHARDS MEDICAL CO (US)
Classification:
- **international:** **A61B17/74; A61B17/86; A61B17/88; A61B17/68; A61B17/88;** (IPC1-7): A61B17/18
- **european:** A61B17/74; A61B17/86P; A61B17/88S
Application number: EP19830300189 19830114
Priority number(s): US19820340093 19820118

Also published as:

 US4530355 (A1)
 EP0085493 (B1)


Cited documents:

 DE2146997
 CH475754
 DE2906068
 US4095591
 US3374786

Report a data error here

Abstract not available for EP0085493
Abstract of corresponding document: **US4530355**

A compression screw assembly for applying compression to a fractured bone includes a lag screw, a compression plate including a hollow barrel member adapted to receive the lag screw in at least one fixed orientation, a wrench assembly adapted to releasably engage the lag screw in axial alignment therewith, and apparatus having surface contours complimentary with the outer surface of the lag screw and inner surface of the barrel member for being optionally insertable into the barrel member to prevent axial rotation of the lag screw with respect to the barrel member.



Data supplied from the **esp@cenet** database - Worldwide

BEST AVAILABLE COPY

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 83300189.4

(51) Int. Cl.³: **A 61 B 17/18**

(22) Date of filing: 14.01.83

(30) Priority: 18.01.82 US 340093

(43) Date of publication of application:
10.08.83 Bulletin 83/32

(84) Designated Contracting States:
AT BE CH DE FR GB LI NL SE

(71) Applicant: **RICHARDS MANUFACTURING COMPANY INC.,**
1450 Brooks Road
Memphis Tennessee 38116(US)

(72) Inventor: **Griggs, Calvin**
1455 Shady Birch
Memphis Tennessee 38116(US)

(74) Representative: **Harrison, Philippa Dinah et al,**
A. A. THORNTON & CO Northumberland House 303-306
High Holborn
London WC1V 7LE(GB)

(84) **Compression screw assembly.**

(67) A compression screw assembly for applying compression to a fractured bone includes a lag screw (20), a compression plate (30) including a hollow barrel member (31) adapted to receive the lag screw (20) in at least one fixed orientation, a wrench assembly (50, 70, 80) adapted to releasably engage the lag screw (20) in axial alignment therewith for introducing the screw (20) into the bone, and means (40) having surface contours complimentary with the outer surface (23) of the lag screw (20) and inner surface (34) of the barrel member (31) for being optionally insertable into the barrel member (31) to prevent axial rotation of the lag screw (20) with respect to the barrel member (31). The means (40) may comprise a clip which has two elongate members which are engageable between flat surface portions (23) on the outer surface of the lag screw and flat surface portions (34) on the inner surface of the barrel member (31) of the compression plate (30) to prevent relative axial rotation between the compression plate (30) and lag screw (20). In use the clip (40) is mounted on the wrench assembly (50, 70, 80) before the lag screw (20) is engaged in the bone and can then be introduced into the barrel member (31) at the option of the surgeon.





FIG. 1.



- 1 -

Compression screw assembly

The invention relates generally to a compression screw assembly for applying a compressive force to a fractured bone.

Workers in the art have devised various
5 compression screw systems for applying compression to a fractured bone. Generally, the systems include a lag screw which extends from the shaft of the bone through the fracture and is anchored in the head of the bone, a compression plate which is adapted to extend over at
10 least a portion of the head of the lag screw and which is anchored to the shaft of the bone and a compression screw which extends from the compression plate to the lag screw to permit the application of a compressive force between the lag screw and the compression plate.
15 It is often desirable to assure that the lag screw is non-rotatably secured to the compression plate. Generally this is accomplished in a keyed system by providing the lag screw with a longitudinally directed keyway, and by providing the portion of the hollow
20 barrel of the compression plate that extends over the head of the lag screw with a corresponding longitudinally directed key. The problem with these systems is that it is difficult to insert the compression plate over the lag screw so that the key and keyway are aligned
25 properly because the lag screw is driven completely

into the bone before the compression plate is inserted.

One method for alleviating the problem of aligning the lag screw and compression plate is to provide an extension attached to the head of the lag screw to permit the lag screw to be aligned with the plate barrel more easily. A second method is to recess the key of the barrel member away from the front end of the barrel member so that the alignment occurs in two distinct steps: first, the aperture of the barrel member of the compression plate is aligned with the lag screw; and second, the key of the barrel member is aligned with the keyway of the lag screw. In a still further method as shown in United States Patent No. 4,095,591, a barrel guide means having an extension member extending outward of the bone and having a cross section similar to that of the lag screw is used so that the barrel member of the compression plate is aligned on the extension member before it is inserted into the fractured bone.

A major disadvantage of the compression screw systems mentioned above is that the surgeon must determine before the insertion of the lag screw whether to use a keyed system or a non-keyed system. If a keyed system is to be used, the lag screw and compression plate must have the keyway and key, respectively. If a non-keyed system is to be used, the lag screw must be able to freely rotate within the barrel of the compression plate.

According to the present invention there is provided a compression screw assembly (10) for applying compression to a fractured bone comprising a lag screw (20) having a first engaging means (23) formed thereon, a compression plate (30) including a hollow barrel member (31) adapted to receive said lag screw in at least one fixed orientation, the interior of said barrel

member having a second engaging means (34) formed thereon;

5 a wrench assembly (50,70,80) adapted to releasably engage said lag screw in axial alignment therewith;

means (40) having surface contours (42) complimentary with said first and second engaging means (23,34) for being optionally insertable into said barrel member to prevent axial rotation of said lag
10 screw with respect to said barrel member.

Advantageously, the components of the compression screw system can be assembled and properly aligned prior to the insertion of the lag screw and compression plate into the bone.

15 The optionally insertable means is preferably a clip which, when inserted between the inner surface of the barrel member and the lag screw, prevents axial rotation of the lag screw with respect to the barrel member of the compression plate as in a keyed system.
20 If the clip is not inserted within the barrel member of the compression plate, the lag screw is able to freely rotate with respect to the compression plate as in a keyless system. The clip may be inserted within the barrel member of the compression plate at the option of
25 the surgeon, and the decision of the surgeon may be reserved until the time when the clip is to be inserted.

Preferably the wrench assembly includes a wrench for releasably engaging the lag screw into the bone, a member for holding the clip in place on the
30 wrench prior to the insertion of the clip into the barrel member of the compression plate, a member for pushing the clip from the holding member into the barrel member of the compression plate between the inner surface of the barrel member and the lag screw, and a stabilizing
35 rod for stabilizing the wrench assembly during the

insertion of the lag screw and compression plate into the fractured bone.

In the preferred embodiment, the contour of the outer surfaces of the lag screw and the wrench are identical and are adapted so that the compression plate, clip, holding member and pushing member which have identical corresponding inner surface contours, can be inserted over the wrench and lag screw in the proper axial alignment. Preferably, the configurations are substantially round and include two flat portions, spaced 180° apart. Thus, the compression screw system can be aligned properly by aligning the flat portions of each member of the assembly.

An embodiment of compression screw assembly will now be described, by way of example only, with reference to the accompanying drawings, in which:-

Figure 1 is a sectional view of an embodiment of a hip screw assembly as installed in a bone, according to the present invention;

Figure 2 is a sectional view of a compression plate of the assembly shown in Figure 1;

Figure 3 is a cross-sectional view of the compression plate shown in Figure 2 taken along the line III-III;

Figure 4 is a top plan view of a clip of the assembly shown in Figure 1;

Figure 5 is a side elevational view of the clip shown in Figure 4;

Figure 6 is a front elevational view of the clip shown in Figure 4;

Figure 7 is a rear elevational view of the clip shown in Figure 4;

Figure 8 is a top plan view of a clip holder for the clip shown in Figure 4;

Figure 9 is a side elevational view of the

clip holder shown in Figure 8;

Figure 10 is a sectional view of the clip holder shown in Figure 9 taken along the line X-X;

Figure 11 is a rear elevational view of the
5 clip holder shown in Figure 8;

Figure 12 is a cross-sectional view of the clip holder shown in Figure 8 taken along the line XII-XII;

Figure 13 is a side elevational view of a clip
10 pusher for the clip shown in Figure 4;

Figure 14 is a cross-sectional view of the clip pusher shown in Figure 13 taken along the line XIV-XIV;

Figure 15 is a top plan view of the clip
pusher shown in Figure 13;

15 Figure 16 is a front elevational view of the clip pusher as shown in Figure 13;

Figure 17 is a top sectional view of the shaft assembly showing the clip pusher, clip holder and clip assembled for installation;

20 Figure 18 side sectional view of the shaft assembly as shown in Figure 17;

Figure 19 is a top view, in partial cutaway, of the hip screw assembly prior to the installation of the hip screw; and

25 Figure 20 is a side view of the hip screw assembly shown in Figure 19;

As shown in the drawings, compression screw assembly 10 consists of lag screw 20, compression plate 30, clip 40, wrench 50, stabilizing rod 60, clip holder
30 70, clip pusher 80 and compression screw 90.

Referring to Figures 1, 19 and 20, lag screw 20 includes a screw head 21 formed at one end of an elongated shaft 22 adapted to be installed into the shaft of the fractured bone, through the fracture, and
35 anchored in the head of the fractured bone. Shaft 22

has a substantially circular cross section with flat portions 23 formed on either side of its outer edge. The second end of lag screw 20 includes drive portion 24. The cross section of drive portion 24 is smaller than that of the remainder of lag screw 20, and is preferably of a modified hexagonal configuration having six sides, one pair of opposing sides being of a different length than the other four sides. Drive portion 24 is adapted to fit within bore 54 of wrench 50 when compression screw assembly 10 is assembled. Lag screw 20 has a bore extending therethrough so that lag screw 20 can be inserted over a guide wire. The inside edge of lag screw 20 contains a threaded portion 25 so that compression screw 90 can be threaded therein. In addition, the threaded portion formed at the lower end of stabilizing rod 60 is inserted within threaded portion 25 when compression screw assembly 10 is assembled.

As shown in Figures 1, 2, 3, 19 and 20 compression plate 30 includes barrel member 31 having a bore 32 extending therethrough of a size that permits bore 32 to accept the second end of lag screw 20 through end 33 of compression plate 30. The inner surface of barrel member 31 includes two flat portions 34 corresponding to flat portions 23 formed on the outer surface of lag screw 20 to permit insertion of clip 40 between flat portions 34 of barrel member 31 and flat portions 23 formed on the outer surface of lag screw 20. Each flat portion 34 includes an indentation 35 adapted to receive a tang 44 of clip 40. End 36 of aperture 32 is adapted to receive compression screw 90 therein. Compression plate 30 also includes a member 37 for enabling compression plate 30 to be anchored to the shaft of the bone. Member 37 contains a plurality of holes 38 for the insertion of bone screws therethrough

- 7 -

in order to anchor compression plate 30 to the shaft of the bone.

Clip 40, illustrated in Figures 1, 4 to 7, and 17 through 19, includes ring 41 having two flat portions 42. The inner surface of ring 41 is of a size that permits ring 41 to accept the second end of lag screw 20 and wrench 50; the outer edge of ring 41 is of a size adapted to permit insertion of clip 40 into bore 32 of barrel member 31 and bore 72 of clip holder 70 that clip 40 can be inserted within bore 32 of barrel member 31 between the outer edge of lag screw 20 and the inner edge of barrel member 31. Two elongated members 43 extend perpendicularly from flat portions 42 of ring 41. Members 43 include tangs 44 which are adapted to be received by indentations 35 formed in the inner surface of barrel 31 of compression plate 30 and grooves 75 of clip holder 70.

Referring to Figures 17 to 20, wrench 50 includes bore 51 adapted to receive stabilizing rod 60. The lower shaft 52 of wrench 50 has an outer surface cross-section adapted to match that of lag screw 20 and includes flat portions 53 which correspond to flat portions 23 of lag screw 20. The end of lower shaft 52 contains drive portion 54, the inner surface of which has a shape corresponding to drive portion 24 of lag screw 20 and is adapted to accept drive portion 24. Depth markings 55, formed in the non-flat portions of wrench 50, are used as assembly 10 is installed in a bone shaft. Lower shaft 52 includes stops 56 formed on its outer surface at its upper end. Stops 56 are protruding portions of lower shaft 52 which are used to prevent premature separation of clip 40 and clip holder 70. The outer edge of upper shaft 57 of wrench 50 is of a larger circumference than that of lower shaft 52 and does not include any flat portions. Upper shaft

57 ends in a T-shaped handle 58. The plane passing through both arms of handle 58 is perpendicular to the plane passing through flat portions 53.

As illustrated in Figures 17 through 20,
5 stabilizing rod 60 is inserted through bore 51 of wrench 50. Stabilizing rod 60 is cannulated so that compression screw system 10 can be threaded over a guide wire to aid in directing the insertion of lag screw 20 into the bone. Stabilizing rod 60 includes a threaded
10 portion at its lower end which can be threaded within portion 25 of lag screw 20. Stabilizing rod 60 also includes knurled end 61.

Clip holder 70, shown in Figures 8 through 12 and 17 through 20, includes an upper barrel portion
15 71 having a bore 72 extending therethrough and two elongated members 73 extending therefrom. The inner surface of clip holder 70 includes flat portions 74. The inner surface of clip holder 70 is adapted to receive clip 40 and includes grooves 75 that receive
20 tangs 44 of clip 40.

Referring to Figures 13 through 20, clip pusher 80 includes barrel portion 81 having a bore 82 extending therethrough, and knurled end 83. Barrel portion 81 includes slots 84 formed in either side. As
25 clip pusher 80 is slid along wrench 50, the lower end of each slot 84 engages a stop 56 to prevent further movement of clip pusher 80 along wrench 50. Ring 85 is disposed within knurled end 83 to frictionally engage upper shaft 57 of wrench 50 as clip pusher 80 is slid
30 along wrench 50. The outer surface of clip pusher 80 includes flat portions 86 at its lower end corresponding to flat portions 74 of clip holder 70.

Compression screw 90, shown in Figure 1, includes threaded shaft 91 which can be threaded into
35 portion 25 of lag screw 20, and includes slot drive 92.

Other well known drives, such as the hex drive, may be used.

In order to assemble compression screw assembly 10, clip pusher 80 is mounted, knurled end 83 first, over the lower shaft 52 of wrench 50 so that flat portions 53 of wrench 50 are aligned with slots 84 of clip pusher 80. Clip pusher 80 is slid along shaft 52 of wrench 50 until slots 84 engage stops 56 of wrench 50 and ring 85 engages upper shaft 57 of wrench 50. Clip 40 then is inserted within bore 72 of clip holder 70 so that flat portions 42 of clip 40 are aligned with flat portions 74 of clip holder 70 and tangs 44 of clip 40 are disposed within grooves 75 of clip holder 70. Elongated members 43 of clip 40 are disposed under elongated members 73 of clip holder 70. Clip holder 70, now containing clip 40, is mounted, barrel portion 71 first, over lower shaft 52 of wrench 50 until clip holder 70 engages clip pusher 80.

Once clip 40, clip pusher 80 and clip holder 70 are in place, compression plate 30 is slid end 36 first, over lower shaft 52 of wrench 50. Wrench stabilizing rod 60 is inserted within bore 51 of wrench 50. The threaded portion of stabilizing rod 60 is threaded within portion 25 of lag screw 20 and drive portion 24 of lag screw 20 is inserted within corresponding drive portion 54 of wrench 50.

To use the above described compression screw system, the surgeon must first insert a guide wire in to the fractured bone, and then use a reamer to ream out the root diameter corresponding to the size of lag screw 20 and the opening for the outside diameter of the barrel member 31 of compression plate 30.

Because stabilizing rod 60 is cannulated, compression screw assembly 10 can be inserted over the guide wire. Lag screw 20 is then threaded partway into

the bone by turning handle 58 of wrench 50. Compression plate 30 is slid forward over insertion wrench 50 and over shaft 22 of lag screw 20 until compression plate 30 is flush against the bone. Lag screw 20 is then
5 threaded fully into the bone to the proper depth as indicated by depth markings 55 on wrench 50.

If lag screw 20 and compression plate 30 are to be inserted so that lag screw 20 is non-rotatably secured to compression plate 30, clip pusher 80 with
10 clip holder 70 and clip 40 attached is pushed forward until clip holder 70 touches and centers on compression plate 30, then pushed again, more firmly, to slide clip 40 from within clip holder 70 and into barrel member 31 of compression plate 30 so that tangs 44 of clip 40
15 become disposed within indentations 35 of barrel member 31. Once clip 40 is in place, clip pusher 80 and clip holder 70 are slipped back down insertion wrench 50. Stabilizing rod 60 is unthreaded from lag screw 20 and wrench 50 and stabilizer rod 60 are removed.

20 Regardless of whether clip 40 is inserted, compression screw 90 may be inserted through barrel 31 of compression plate 30 and threaded into threaded portion 25 of lag screw 20 to obtain a tight compression between lag screw 20 and compression plate 30. Once
25 the desired amount of compression has been achieved, compression screw 90 may be removed or left in place at the option of the surgeon.

Finally, compression plate 30 is anchored to the bone by inserting bone screws through apertures 38
30 of member 37 and into the bone.

There is thus provided a compression screw assembly wherein the parts are properly aligned and installed and thereafter the lag screw may be non-rotatably secured to the compression plate at the option of the
35 surgeon.

CLAIMS:

1. A compression screw assembly (10) for applying compression to a fractured bone comprising a lag screw (20) having a first engaging means (23) formed thereon, a compression plate (30) including a hollow barrel member (31) adapted to receive said lag screw in at least one fixed orientation, the interior of said barrel member having a second engaging means (34) formed thereon;

a wrench assembly (50,70,80) adapted to releasably engage said lag screw in axial alignment therewith;

means (40) having surface contours (42) complimentary with said first and second engaging means (23,34) for being optionally insertable into said barrel member to prevent axial rotation of said lag screw with respect to said barrel member.

2. A compression screw assembly as claimed in claim 1, wherein said wrench assembly (50,70,80) is adapted to be assembled together with said lag screw (20), said compression plate (30) and said optionally insertable means (40) so that all portions of the compression screw assembly are axially aligned prior to the insertion of the compression screw assembly into a fractured bone.

3. A compression screw assembly as claimed in either claim 1 or claim 2, wherein said optionally insertable means is a clip (40) adapted to be slidably mounted on said wrench assembly (50).

4. A compression screw assembly as claimed in claim 3, wherein said wrench assembly (50,70,80)

comprises a wrench (50) having means (53) for releasably engaging said lag screw (20) in axial alignment therewith, a pushing member (80) slidably mounted on said wrench and in axial alignment therewith, for inserting said clip (40) into said barrel member, and a holding member (70) slidably mounted on said wrench and in axial alignment therewith, for holding said clip (40) in place on said wrench while said lag screw is being installed in a bone and until said clip is to be inserted into said barrel member.

5. A compression screw assembly as claimed in claim 3, wherein said wrench assembly comprises a wrench (50) and a holding member (70) slidably mounted on said wrench for holding said clip (40) in place while the lag screw (20) and compression plate (30) are being installed and until the clip is to be inserted in the hollow barrel member (31) of the compression plate (30).

6. A compression screw assembly as claimed in either claim 3 or claim 5, wherein said wrench assembly comprises a pushing member (80) slidably mounted on said wrench (50) for pushing said clip in the hollow barrel member of the compression plate.




7. A compression screw assembly as claimed in any one of the preceding claims, wherein said lag screw comprises means (24) for coacting with said wrench assembly so that said lag screw can be releasably engaged by the wrench assembly in axial alignment therewith.

8. A compression screw assembly as claimed in any one of the preceding claims wherein said lag screw (20) has an outer surface contour which so corresponds to










the respective surface contours of the other portions of the compression screw assembly that the compression screw assembly can be assembled and axially aligned prior to the insertion of the lag screw into the bone.

9. A compression screw assembly as claimed in any one of the preceding claims, wherein said barrel member (31) of said compression plate includes an inner surface contour which so corresponds to the respective surface contours of the other portions of the compression screw assembly that the compression screw assembly can be assembled and axially aligned prior to the insertion of the lag screw (20) into the bone.

10. A compression screw assembly as claimed in any one of the preceding claims, wherein said wrench assembly (50,70,80) comprises means for releasably engaging said lag screw, said engaging means being capable of rotating the lag screw when engaged therewith.



2/5



3/5




FIG. 13.




FIG. 14.




FIG. 16.




FIG. 15.

4/5







FIG. 17.



5/5





European Patent
Office

EUROPEAN SEARCH REPORT

0085493
Application number

DOCUMENTS CONSIDERED TO BE RELEVANT			EP 83300189.4
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 7)
X	DE - B1 - 2 146 997 (AESCULAP WERKE AG) * Fig.; column 3, lines 5-37; column 5, line 1 - column 6, line 34 * --	1,7-10	A 61 B 17/18
A	CH - A - 475 754 (PAUL KLEUSER CHIR. INSTR.) * Totality * --	1,8,9	
A	DE - A1 - 2 906 068 (SYNTHES AG) * Fig. 2,3,6-10,13; page 12, last paragraph - page 15, first paragraph; pages 20,21 * --	1,7-10	
A,D	US - A - 4 095 591 (M. GRAHAM, T.L. CRAIG) * Fig.; column 5, line 57 - column 6, line 41 * --	1,7-10	TECHNICAL FIELDS SEARCHED (Int. Cl. 7) A 61 B 17/00
A	US - A - 3 374 786 (G.R. CALLENDER) * Fig. 1-6,10; column 2, line 24 - column 3, line 62 * ----	1,7-10	
The present search report has been drawn up for all claims			
Place of search VIENNA		Date of completion of the search 13-05-1983	Examiner LUDWIG

CATEGORY OF CITED DOCUMENTS

X : particularly relevant if taken alone
Y : particularly relevant if combined with another document of the same category
A : technological background
O : non-written disclosure

T : theory or principle underlying the invention
E : earlier patent document, but published on, or after the filing date
D : document cited in the application
L : document cited for other reasons

& : member of the same patent family, corresponding

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.